HWM Global

Innovations that keep critical resources flowing.

hwmglobal.com
+44 (0)1633 489479

Incident Logger

Data Logging System

Incident Logger (based upon the advanced Multilog LX2) is a highly versatile data collection system designed for incidences where large amounts of data are required in a short space of time.

Using a GPS module and a quick start design, the Incident Logger can be rapidly deployed without software or PC cables, generating site specific data in moments and allowing for targeted work in the affected area.

Designed to fit inside very shallow Atplas boxes or hydrant installation, Incident Logger is designed for rapid deployment, with no software or PC cables required for installation.

Applications

Quick installation with automatic GPS ref, zero pressure transducer and signal strength test. No operator skill or PC software required for deployment or retrieval.

Data viewed via HWM Online instantly, ideal for Incident Control Rooms to see exactly what is happening on the network quickly, especially in incident response. Loggers can be connected to an external battery pack for fast dial in communications.

Key Features

- **Automatic location:** in-built GPS module automatically generates location data.
- **Pulse interval timing:** smooths reading set times of infrequent pulses e.g. minimum night flow.
- **Versatile logging:** up to 2x digital flow inputs and 1x analogue input (internal pressure, external pressure or 4-20mA).
- **Telemetry:** NBIoT LTE-based cellular communication as standard with fallback 2G capability.
- **Flexible:** up to 25Hz and window logging (on request).
- **Fast logging:** logging to 1 second - as standard.
- **Multiple recordings:** can record mixture of minimum, maximum, average or spot values in each sample interval.
- **Detailed readings:** true man and min flow and investigation of flow spikes through Pseudo logging.
- **Serial input:** for connection to digital meters, SonicSens 3 level sensor, PermaLog+ leak noise logger and Modbus sensors.
- **Long-term monitoring:** 5 year battery life (depending on settings and signal strength).
- **External antennas:** support improved signal strength (contact HWM Global for more information).
- **Fully waterproof:** the IP68 rating has been tested at 10m depth over a 24 hour period.
- **Alarms:** real-time alarms can be enabled for immediate response to network incidents.

HWM Global

Innovations that keep critical resources flowing.

hwmglobal.com
+44 (0)1633 489479

Incident Logger

Data Logging System

Input Options

Digital: One bi-directional pulse for Flow.
Two single-directional pulse inputs for Flow logging.
Up to 64 pulses per second

Analogue: Internal Pressure Transducer. External pressure. 4-20mA (optional).
0-20 bar / 0-200 meters head / 0-300psig, 0.1% repeatability / please note that the logger is calibrated to 10 bar as standard. (20 bar calibration must be specified at time of order if required).
(0-10 bar / 0-100 meters head / 0-150 psig option also available).

Serial Input: Proprietary serial interface for SonicSens 3 ultrasonic level monitors, Permalog+ leak noise loggers, Serial meters etc. Modbus for third-party devices.

Communication

Local: Infra-red reading head for connection to laptop, desktop PC or Windows tablet.

Internal Cellular Modem: Cellular modem supporting 5G/NBIoT or 4G/LTE Cat-1.

Accelerated Dial-in: Dial-in rate is increased if alarm situation is triggered. Logger can accelerate dial-in at alarm level for multiple applications - including SonicSens 3, Flow, Pressure and other alarmed sensors.

Specifications

Sampling Rate: Variable sample rate 1s to 24hrs, accelerating on alarm.

Logger/ Site ID: Readable factory set serial number in firmware.

Dimensions: 110H x 150W x 105D (mm) - 4.3" x 5.9" x 4.1"

Construction: PC/ABS plastic enclosure.

Weight: 590g (1.3lb).

Operating Temp: -20 to +60°C (-5 to +140°F).

Ingress Protection: IP68 submersible.

Power: Lithium Thionyl-Chloride, typical 5 years (depending on settings and signal condition). External power connection for battery box and third-party devices.

Memory: Primary recording: 1 million readings (non-volatile memory)

Fast Logging (secondary channel): Secondary, fast channel supports sampling up to 25 Hz and record average, minimum, maximum, standard deviation or time interval between pulses (for data smoothing).

Pulse Interval Timings: Count and Event logging modes independent for both recordings. Pulse Interval Timing helps to smooth readings (e.g. leakage) in low flows by counting the time between each pulse (event mode). This is available in addition to totalling the pulses (count mode).

Alarms: Multiple alarm options including Rate of Change, Profile, Minimum Night Flow and Threshold. 16 alarms per logger. Can be programmed to auto dial up to 8 telephone numbers on alarm. Over 16 alarms per logger depending on channel configuration.

ISO 9001 QUALITY MANAGEMENT
ISO 14001 ENVIRONMENTAL MANAGEMENT
ISO 27001 INFORMATION SECURITY MANAGEMENT
ISO 45001 HEALTH & SAFETY MANAGEMENT
CYBER ESSENTIALS

HWM-Water Limited (Trading as HWM Global). Registered in England and Wales Number 01463016
and registered office is Ty Coch House | Llantarnam Park Way | Cwmbran | NP44 3AW | UK
DAT-146-0001-B 27.02.2026

A Halma company