

Data Loggers

Data Logger Comparison



Multilog 2

Multilog LX2

COMlog 2

LoLog Vista

LoLog 450

	Multilog 2	Multilog LX2	COMlog	LoLog Vista	LoLog 450
Channels	8 Pulses 4 Analog	4 Pulses 2 Analog	4 Pulses 1 Analog	1 Analog 1 Digital	1 Analog 1 Digital
Configuration	Any of 4 Bulkhead or Pressure	2 Bulkhead or Gland + 1 Pressure	1 Bulkhead or Gland	2 Bulkhead or 1 Bulk + 1 Pressure	2 Bulkhead or 1 Bulk + 1 Pressure
Pseudo Channel	Yes	Yes	No	No	No
Remote Access	Yes	Yes	Yes	No	No
Dimensions (mm)	257H x 129W x 77D	110H x 150W x 105D	84H x 115W x 114D	160H x 108W x 45D	92H x 126W x 44D
Weight	1.6kg	590g	570g	800g	210g
Operating Temp.	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C
Protection	IP68 submersible	IP68 submersible	IP68 submersible	IP68 submersible	IP68 submersible
Memory	2 million readings	1 million readings	1 million readings	64,000 readings	64,000 readings
Frequency	Variable logger sample rate from 1s to 24hrs	Variable logger sample rate from 1s to 24hrs	Variable logger sample rate from 1s to 24hrs	Variable logger sample rate from 1s to 24hrs	1 second increments from 1 to 60 seconds
Data Transfer	GSM + SMS	GSM + SMS	GSM + SMS	RS232 by IR	RS232 by IR

MONITORING ASSETS, DELIVERING DATA, BRINGING CONTROL



HWM Water Ltd
Ty Coch House, Llantarnam Park Way
Cwmbran, NP44 3AW
United Kingdom

Tel: +44 (0) 1633 489 479
Fax: +44 (0) 1633 877 857
E-mail: sales@hwm-water.com
Web: www.hwmglobal.com

