

Multilog IS

Multi-Input, Multi-Application ATEX Telemetry Data Logger

Multilog IS is an intrinsically safe and highly-versatile telemetry data logging platform designed for compatibility with a wide variety of HWM and third-party sensors (including: MicroFlow-i, dBi or VEGAPULS) at the same time.

Multilog IS is capable of connecting via LTE-M or NBIoT with 2G fallback for dependable data telemetry and future-proofing in the rapidly evolving cellular landscape.

The unit offers multiple inputs and switch outputs and is ideally suited to installation in environments where corrosion is a concern. Bluetooth® connectivity allows for re-programming via a mobile app, making in-situ updates much easier and cost-effective.



Key Features and Benefits

- **Telemetry:** NBIoT/LTE-M based cellular communication as standard with fallback 2G capability
- **Intrinsically Safe:** certified for use in Zone 0 hazardous areas (visit HWM website for certification details)
- **Serial and Analogue input options:** for connection to SonicSens 3 ultrasonic level sensor, external pressure transducers, active/passive 4-20mA, voltage, digital pulses, Modbus, SDI-12
- **Various sensor connections:** up to 16 channels
- **Alarm:** highly configurable alarms
- **Robust:** drop tested plastic housing and connectors to prevent corrosion in harsh environments
- **External antennas:** support improved signal strength - contact HWM for information of our wide-ranging options
- **Bluetooth® connectivity:** local Bluetooth® configuration through Deployment App
- **Fully waterproof:** the IP68 rating has been tested at 10m depth over a 24 hour period
- **Remote upgrades:** firmware and programming changes made remotely for efficiency and cost-effectiveness
- **Control outputs:** pulse inputs or trigger on alarm, allows operation of third-party sensors, e.g. water samplers
- **Long-term monitoring:** up to 5 year battery life
- **External battery option:** external battery input to support accelerated dial-in or powering of third-party sensors

Applications

With multiple input capability, Multilog IS is a highly effective, battery powered data logging/RTU solution. Applications include:

- Level, Velocity and Flow monitoring
- Water Quality Monitoring
- Control Outputs for third-party systems (e.g. water sampler)
- Modbus and SDI12 sensor telemetry
- External power options

Multilog IS has been design-matched to numerous ATEX-rated sensors, ensuring ATEX certification for a wide variety of sensor configurations.

MONITORING ASSETS, DELIVERING DATA, BRINGING CONTROL

Multilog IS

Multi-Input, Multi-Application ATEX Telemetry Data Logger

Input Options

Serial	HWM SonicSens 3 ultrasonic level sensor. Third party sensors using Modbus or SDI12 communication protocol. I ² C interface.
Analogue	External pressure transducer (contact HWM for more details) Voltage (0-1V or 0-10V) Passive or active 4-20mA Temperature
Digital	Inputs for float switches, positional indicators, magnetic switches for state indication, outputs for the Control of Water Samplers or externally controlled sensors

Features

Sample Frequency	Variable logger sample rate from 1s to 24hrs (this may affect battery life and communication costs)
Dimensions	239H x 319W x 100D (mm) 9.4" x 12.6" x 3.9"
Construction	PC/ABS plastic enclosure
Weight	Maximum: 3.8kg (8.4lb)
Operating Temp.	-20 to +60°C (-5 to +140°F)
Ingress Protection	IP68 submersible
Power	Internal Battery: 7.2V External Battery: 10.8V Sensors are powered by data logger or optional additional external battery packs
Memory	Standard recording: 1 million readings
Alarms	Multiple alarm options including Rate of Change, Profile, Minimum Night Flow and Threshold. Over 16 alarms per logger depending on channel configuration. Multiple alarm destinations can be set in DataGate.
Inputs	Up to 16 channels for various sensor connections

Communication

Local	Bluetooth® connectivity for configuration using our mobile app
Internal Cellular Modem	Cellular modem supporting 2G/ NBIoT/LTE-M (Cat-M1). SMS onward forwarding service available - contact HWM for available options. Multilog IS can send data down to every 15 mins, with appropriate battery pack
Accelerated dial-in	Dial-in rate is increased if alarm situation is triggered. Logger can accelerate dial-in at alarm level for multiple applications - including SonicSens 3, Flow, Pressure and other alarmed sensors.



All images, text and designs are protected by international and UK copyright law and remain the property of HWM Global. It is against the law to copy or use any of the content from the HWM Global website or literature without the written consent of HWM Global. HWM-Water Ltd. reserve the right to vary the specification.



HWM Global

Ty Coch House
Llantarnam Park Way
Cwmbran
NP44 3AW
United Kingdom

Tel: +44 (0) 1633 489 479
Email: sales@hwmglobal.com
Web: www.hwmglobal.com

MONITORING ASSETS, DELIVERING DATA, BRINGING CONTROL