Dipole 2G/3G/4G/NBIoT/LTE-M (Cat-M1)⁺ Antenna



Antenna

Frequency Range	850/900/1700/1800/1900/2100MHz
Polarization	Vertical
Gain	3dBi
Impedance	50Ω
Dimensions	160 x 45 mm

⁺Contact HWM to confirm worldwide coverage of NBIoT and LTE-M (Cat-M1)

Environmental

Operating Temp.	-20°C - +60°C
Ingress Protection	IP68
Environmentally Friendly	ROHS Compliant

Mechanical

Cable	RG58
Connector	FME or Bulgin
Mounting Method	Magnetic







 WASTE WATER

 Product Code
 AER8035-1

Bulgin



Connector

All images, text and designs are protected by international and UK copyright law and remain the property of HWM. It is against the law to copy or use and of the content from HWM website or literature without the written consent of HWM. HWM Ltd. reserve the right to vary the specification.



HWM Water Limited

Ty Coch House Llantarnam Park Way Cwmbran NP44 3AW United Kingdom

Tel:	+44 (0) 1633 489 479
Fax:	+44 (0) 1633 877 857
Email:	sales@hwm-water.com
Web:	www.hwmglobal.com

MONITORING ASSETS, DELIVERING DATA, BRINGING CONTROL

www.hwmglobal.com