Magpot 2G/3G/4G/NBIoT/LTE-M (Cat-1) Antenna



Electrical Characteristics

Frequency (MHz)	698-960/1710-2655MHz
V.S.W.R	<3.0
Gain (Zenith)	2dBi
Polariztion	Vertical
Impedance	50Ω
Radiation	All Directional
Dimensions	61 x Ø33 mm

^{*}Contact HWM to confirm worldwide coverage of NBIoT and LTE-M (Cat-1)

Mechanical Characteristics

Connector	FME or Bulgin
Cable	RG174
Height	61mm +/-3mm
Mounting Method	Magnetic

Environmental Characteristics

Operating Temperature	-40°C ~ +85°C
Ingress Protection	IP68
Environmentally Friendly	ROHS Compliant







Product Code	CABA8110-7 (5m cable length)*
Connector	FME

^{*} additional cable lengths are available on request



Product Code	CABA9498 (2m cable length)*
Connector	Bulgin

^{*} additional cable lengths are available on request




All images, text and designs are protected by international and UK copyright law and remain the property of HWM. It is against the law to copy or use and of the content from HWM website or literature without the written consent of HWM. HWM Ltd. reserve the right to vary the specification.











HWM Water Limited

Ty Coch House Llantarnam Park Way Cwmbran NP44 3AW United Kingdom

Tel: +44 (0) 1633 489 479 Fax: +44 (0) 1633 877 857 Email: sales@hwm-water.com Web: www.hwmglobal.com

MONITORING ASSETS, DELIVERING DATA, BRINGING CONTROL