

# DXmic

## Ground Microphone

DXmic is the latest generation ground microphone from HWM. Building on the excellent reputation of the Xmic, the DXmic features touch screen operation and a wealth of new innovative features.

The DXmic has the highest sound quality and records leak noise data so that the position of leaks will be pinpointed quickly.

The device comes with a robust carry case which can also be used as a charging station



### Key Features and

- **Excellent audio:** Best in class sound quality
- **Durable:** Robust housing with carry strap fixings
- **Colour touch screen:** Clear multifunctional graphics and ease of use
- **Wireless capability:** For headphones or transfer of audio/configuration data to PC (Wireless or standard headphone options)
- **Frequency display:** For each analysis and filter setting
- **Flexible:** Auto and manual filters
- **Clear upgrade path:** Compatible with Xmic foot and handprobe sensor
- **USB capability:** For data transfer and firmware updates
- **Long battery life:** Li-ion cells with up to 15-25 hrs Battery life
- **User friendly:** Safety Noise Level cut off and leak noise isolation filters
- **Minimum level noise recording and display:** For effective pinpointing

### Applications

DXmic is the latest generation ground microphone, giving the highest sound quality for accurate location of leaks on site.

The latest digital features, such as frequency analysis and frequency shifting able use in the most challenging environments and in low frequency (plastic pipe) situations.

The colour touch screen makes the unit easy to use whilst enabling multiple signals and frequency displays.

Compatibility with Xmic sensors gives an upgrade path for existing HWM ground microphone users.

MONITORING ASSETS, DELIVERING DATA, BRINGING

# DXmic

## Ground Microphone

### Features

Frequency range	0 to 5000Hz
Battery life	Minimum 25 hours (with battery saving) 15 hours (constant)
Battery charge	Maximum 8 hours.
Charger	Universal 110-240V AC mains charger with 12V DC output (Optional in car adapter) all items can be charged in case .USB socket for lead phone charging
Weight	600g (with batteries)
Temperature	Operating temperature range -15C to +50C
Dimensions	193H x 109W x 60D mm (7.5"H x 4.2"W x 2.3"D).
Keypad	Touch screen LCD
Display	5.0 inch TFT LCD colour
Ingress protection	IP65
Headphone connection	Wireless or cable connection. With safety noise cut off
Headphones	Bluetooth linked or Studio quality headphones are supplied as standard Aviation quality headphones are available as an option
Rmic ground microphone	High sensitivity piezo-electric sensor mounted in windproof, nitrile rubber housing. Low noise 1.5 m cable Weight: 2.9kg
Hand probe Attachment optional	The hand probe is supplied with a tripod foot and two aluminium probe rods for sounding in soft ground plus magnetic contact for better coupling to fittings each probe rod is 400mm in length
Displays	<ul style="list-style-type: none"><li>- Filter selection with noise level indicator and frequency analysis</li><li>- Minimum level profiling</li><li>- Device settings</li></ul>



All Images, text and designs are protected by international and UK copyright law, and remain the property of HWM. It is against the law to copy or use any of the content from HWM website or literature without the written consent of HWM. HWM Water Ltd. reserve the right to vary the specification. **Issue 1. 06:2017**

### HWM Water Limited

Ty Coch House  
Llantarnam Park Way  
Cwmbran  
NP44 3AW

Tel: +44 (0) 1633 489 479  
Fax: +44 (0) 1633 877 857  
Email: [sales@hwm-water.com](mailto:sales@hwm-water.com)

MONITORING ASSETS, DELIVERING DATA, BRINGING

[www.hwmglobal.com](http://www.hwmglobal.com)

MAN-150-0002-A