

# Multilog IS

## Multi-Input, Multi-Application ATEX Telemetry Data Logger

Multilog IS is an intrinsically safe and highly-versatile telemetry data logging platform designed for compatibility with a wide variety of HWM and third-party sensors (including: MicroFlow-i, dBi or VEGAPULS) at the same time.

Multilog IS is capable of connecting via LTE-M or NBIoT with 2G fallback for dependable data telemetry and future-proofing in the rapidly evolving cellular landscape.

The unit offers multiple inputs and switch outputs and is ideally suited to installation in environments where corrosion is a concern. Bluetooth® connectivity allows for re-programming via a mobile app, making in-situ updates much easier and cost-effective.



### Key Features and Benefits

- **Telemetry:** NBIoT/LTE-M based cellular communication as standard with fallback 2G capability
- **Intrinsically Safe:** certified for use in Zone 0 hazardous areas (visit HWM website for certification details)
- **Serial and Analogue input options:** for connection to SonicSens 3 ultrasonic level sensor, external pressure transducers, active/passive 4-20mA, voltage, digital pulses, Modbus, SDI-12
- **Various sensor connections:** up to 16 channels
- **Alarm:** highly configurable alarms
- **Robust:** drop tested plastic housing and connectors to prevent corrosion in harsh environments
- **External antennas:** support improved signal strength - contact HWM for information of our wide-ranging options
- **Bluetooth® connectivity:** local Bluetooth® configuration through Deployment App
- **Fully waterproof:** the IP68 rating has been tested at 10m depth over a 24 hour period
- **Remote upgrades:** firmware and programming changes made remotely for efficiency and cost-effectiveness
- **Control outputs:** pulse inputs or trigger on alarm, allows operation of third-party sensors, e.g. water samplers
- **Long-term monitoring:** up to 5 year battery life
- **External battery option:** external battery input to support accelerated dial-in or powering of third-party sensors

### Applications

With multiple input capability, Multilog IS is a highly effective, battery powered data logging/RTU solution. Applications include:

- Level, Velocity and Flow monitoring
- Water Quality Monitoring
- Control Outputs for third-party systems (e.g. water sampler)
- Modbus and SDI12 sensor telemetry
- External power options

Multilog IS has been design-matched to numerous ATEX-rated sensors, ensuring ATEX certification for a wide variety of sensor configurations.

# Multilog IS

## Multi-Input, Multi-Application ATEX Telemetry Data Logger

### Input Options

|          |  |
|----------|--|
| Serial   | HWM SonicSens 3 ultrasonic level sensor. Third party sensors using Modbus or SDI12 communication protocol. I <sup>2</sup> C interface.                               |
| Analogue | External pressure transducer (contact HWM for more details)<br>Voltage (0-1V or 0-10V)<br>Passive or active 4-20mA<br>Temperature                                    |
| Digital  | Inputs for float switches, positional indicators, magnetic switches for state indication, outputs for the Control of Water Samplers or externally controlled sensors |

### Communication

|                         |  |
|-------------------------|--|
| Local                   | Bluetooth® connectivity for configuration using our mobile app   |
| Internal Cellular Modem | Cellular modem supporting 2G/ NBIoT/LTE-M (Cat-M1). SMS onward forwarding service available - contact HWM for available options.<br><br>Multilog IS can send data down to every 15 mins, with appropriate battery pack |
| Accelerated dial-in     | Dial-in rate is increased if alarm situation is triggered. Logger can accelerate dial-in at alarm level for multiple applications - including SonicSens 3, Flow, Pressure and other alarmed sensors.                   |

### Features

|                    |   |
|--------------------|---|
| Sample Frequency   | Variable logger sample rate from 1s to 24hrs (this may affect battery life and communication costs)   |
| Dimensions         | 239H x 319W x 100D (mm)<br>9.4" x 12.6" x 3.9"  |
| Construction       | PC/ABS plastic enclosure  |
| Weight             | Maximum: 3.8kg (8.4lb)  |
| Operating Temp.    | -20 to +60°C (-5 to +140°F)   |
| Ingress Protection | IP68 submersible  |
| Power              | Internal Battery: 7.2V<br>External Battery: 10.8V<br><br>Sensors are powered by data logger or optional additional external battery packs   |
| Memory             | Standard recording: 1 million readings  |
| Alarms             | Multiple alarm options including Rate of Change, Profile, Minimum Night Flow and Threshold. Over 16 alarms per logger depending on channel configuration. Multiple alarm destinations can be set in DataGate. |
| Inputs             | Up to 16 channels for various sensor connections  |



All images, text and designs are protected by international and UK copyright law and remain the property of HWM. It is against the law to copy or use any of the content from HWM website or literature without the written consent of HWM. HWM Ltd. reserve the right to vary the specification.



### HWM Water Limited

Ty Coch House  
Llantarnam Park Way  
Cwmbran  
NP44 3AW  
United Kingdom

+44 (0) 1633 489 479  
sales@hwm-water.com  
www.hwmglobal.com

MONITORING ASSETS, DELIVERING DATA, BRINGING CONTROL