HWM-Water Itd

AQUAFLUSH INSTALLATION GUIDE

MAN-535-0003-A

A Crosbie

Document Control

Issue	Details	Author	Date
А	Initial release	AC	04/02/2014



AquaFlush Setup Guide Version 1



Warning: This manual contains important safety and operating information. Please read, understand and follow the instructions in the manual.

Installing Legion dual unit



1. Connect flush system

- 2. Run SW-535-0001__Aquaflush Programmer
- 3. Select com port for 553-010 (fig.1)
- 4. Enter unit ID (fig.2)
- 5. Click on get configuration (fig.3) then hold magnet on test point of the unit for 3 to 5 seconds. Status window (fig.4) should read **configuration received**.
- 6. Update the following fields: Test Days, Valve Option, Valve Open Times and Working Hours. (fig.5)
- Click configure unit (fig.6) then hold magnet on test point for 3 to 5 seconds. Status window should read ACK Received – Unit Configured.

MAN-535-0003-A (Version 1)

- Hold magnet on test point again for 3 to 5 seconds status window should read **Time received Unit Clock Configured**. Click start test (fig.7) then hold magnet on test point for 6 seconds unit 8.
- 9. should run flush test.
- Status window should read Pass or Fail after test. 10.

0					×
Communications Port © 0ff ◯ 1 ◯ 2 ◯ 4 1	a	n aquavisi@n	Unit ID 0 0	Received Time	Temperature
11:23:27	Test days Sunday Monday Tuesday Wednesday Thursday Friday Saturday	Valve Option Single Dual Valve Open Times (minutes) Cold Hot I Valve Open Times (minutes) Valve Open Times (minutes) Valve Option Valve	0 0 0 0 0 0 0 0 0 0 0		
	Reference IDs	0			
Cold Inlet de		Enable Logging File Path C:\logger\ Start Test	0 0 0 0		
		7	0		

HWM-Water Ltd Ty Coch House Llantarnam Park Way Cwmbran NP44 3AW United Kingdom +44 (0)1633 489479 www.HWM-water.com

MAN-535-0003-A (Version 1)

